


SPF5000S Specification Sheet




Accessories to consider...

Stop/no entry signs
(hgv height also available)



Pogotip end supports
(drop down)



Specification:

Maximum boom length:

7.0metres

Boom diameter:

76mm

Finish:

Zinc coated and polyester powder coated.

Dimensions:

120mm square

Optional extras:

- bottom skirting
- stop/no entry signs

Comes complete with:

- lock-able end rest
- padlock
- anchor shield bolts
- lifting handle

The SPF5000S Standard Manual Raise Arm barrier

The SPF5000s manual raise arm barrier is a low maintenance cost effective way of manually controlling access to unauthorised areas It covers roadway spanning up to 7 metres.

The pivot assembly is made of steel box section, The shaft is zinccoated pivoting on two heavy duty stainless steel bearing blocks.

Aluminium arm finished in either alternate red and white or alternate yellow and black vinyl hatching (other colours available).

The design of the SPF5000s also comes with a spring loaded locking mechanism allowing you to fix the barrier in the raised and lowered position prior to applying the padlock. It also incorporates a counter balanced fish tail weight which is fine tuned for ease of operation.

Dual barriers are available with

a central locking mechanism to suit wider spans.

The SPF5000s comes complete with a lock-able end rest, padlock and keys.

No mounting plate is required as m16 anchor shield bolts are also included.

Each barrier can be custom designed to suit your company, with a variety of colour schemes available.

Standard colours:
Red/white or yellow/black.

EVERY EFFORT HAS BEEN MADE IN PREPARATION OF THIS SHEET HOWEVER WE HOLD NO RESPONSIBILITY FOR ERRORS OR OMISSIONS.