

SPF8000A Specification Sheet



Specification:

CE approved

Product description:

Hydraulic operation

Manufactured from welded rectangular hollow section frame and durbar top plate

Galvanised steel

Emergency lower incorporated as standard

Power requirement:

Single phase 230v or 3 phase 400v

Height:

340mm or 500mm or 800mm

Length:

Available in half-width sizes from 2 – 5 metres

Weight capacity:

Maximum 12 tonnes on standard kerbs

(Higher capacities available on request)

Operation time:

4.0 – 6.0 secs (dependant on version)

Finish:

Galvanised & painted in yellow and black (high visibility)



The SSPF8000A Automatic

The SSPF8000A automatic rising kerb is tough, reliable and uncompromising.

It provides the perfect solution for prevention of unwanted vehicle access in both manned and unmanned vehicle parking areas. The kerb also provides an excellent deterrent against the most determined intruder.

The kerb is manufactured from welded rectangular hollow section frame and durbar top plate it also features an advanced hydraulic power pack to raise and lower the unit smoothly.

A state of the art

programmable logic controller coordinates the hydraulics, access control and traffic light signalling system. An intelligent back up system fitted as standard, ensures that an emergency lowering facility is operational during power failure.

The kerb offers a variety of access control options including proximity card, remote fob, token acceptor, keypad and intercom, working in conjunction with inductive loop sensors, ensuring

EVERY EFFORT HAS BEEN MADE IN PREPARATION OF THIS SPECIFICATION SHEET. HOWEVER, WE HOLD NO RESPONSIBILITY FOR ERRORS OR OMISSIONS.

safety and close function